



World-class platform lift
NTD A300S - PP SRBK PORTAL
(UKRAINE) - www.tehportal.com.ua
tel +3-8-063-024-65-92





NTD A300S - The platform lift which improves your home and makes everyday life easier!

- Especially designed for private homes and small spaces
- A wide range of accessories and options
- Safe and easy usage
- Easy installation and maintenance
- Certified quality product

Our new mini-sized platform lift: NTD A300S is especially designed for private homes and apartment buildings. With a wide range of options and accessories the lift will not only blend into your home, it will complement it!

For almost any living space where you need freedom and increased accessibility, NTD A300S is a great solution. Choose NTD A300S to improve your life quality and increase value of your home.

- A variety of accessories and options
- Standard steel shaft in off white RAL 9016 or glazed shaft panels as option
- Steel doors with panoramic window as standard
- Exclusive aluminium doors as option
- A variety of optional RAL colours

Comfortable & easy to use

Simply press the hold-to-run button and the lift will take you to another level. Silent, easy to use and well integrated. You will be happy with your choice of NTD A300S in your home.

High quality & safety

Safety edges, emergency lighting and an alarm button guarantees that you feel completely safe.

Easy installation

Installation is done within a few days thanks to the pre-prepared construction kit. No pit is necessary and the lift can be floor mounted without causing any damage to your home.

TECHNICAL FACTS - NTD A300S	
Rated load	300 kg
Rated speed	9 m/min (0,15 m/s)
Lifting height	max 4 landings, 13 meters
Platform dimensions	830 x 800 (depth x width, mm)
Footprint dimensions	930 x 1200 (depth x width, mm)
Shaft	Standard steel panels or glazed panels as option
Door configuration	Single-entry, open through (A & C-side)
Doors	Single hinged doors Standard steel door fronts painted off white RAL 9016 Aluminium door fronts in natural anodized aluminium Fire and gas resistant doors EI60
Door dimensions	700 x 2000 mm (steel door)
Gate dimensions	700 x 1100 mm (lifting height < 3 m)
Control system	Micro computer based control system
Power supply, standard " , optional	400 V, 3-phase 50/60 Hz, 16 A starting current 230 V, 1-phase, frequency converter, soft start & stop 400 V, 3-phase frequency converter, soft start & stop
Motor power	2,2 kW
Options	Telephones, locking systems, automatic door openers, elbow buttons, electric battery lowering, IR-control, automatic shaft lighting, arrival bells, level indicator
<p>NTD A300S is EC-type tested and certified by the Notified Body DNV, according to the European Machinery Directive 2006/42/EC for new buildings and the European Standard for platform lifts EN 81-41 for existing buildings.</p>	

